



**SAFETY DATA SHEET**  
EXTRA GLOSS PROTECTION

Page: 1

Compilation date: 05/10/2004

Revision date: 23/04/2015

Revision No: 12

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product name: EXTRA GLOSS PROTECTION

Product code: No.1/SOL/5103

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of substance / mixture: Polish for use on motor vehicle bodies

**1.3. Details of the supplier of the safety data sheet**

Company name: AUTOGLYM

Works Road

Letchworth

Herts

SG6 1LU

UK

Tel: +44 (0) 1462 677766

Fax: +44 (0) 1462 677712

Email: [sds@autoglym.co.uk](mailto:sds@autoglym.co.uk)

**1.4. Emergency telephone number**

Emergency tel: +44 (0) 1462 489498 (24Hrs)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

Classification under CHIP: -: R10; Xn: R65; -: R66; -: R67

Classification under CLP: STOT SE 3: H336; Asp. Tox. 1: H304; Flam. Liq. 3: H226

Most important adverse effects: Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**2.2. Label elements**

Label elements under CLP:

Hazard statements: \* H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

Signal words: \* Danger

Hazard pictograms: \* GHS02: Flame

[cont...]

**SAFETY DATA SHEET**  
EXTRA GLOSS PROTECTION

Page: 2

GHS07: Exclamation mark

GHS08: Health hazard



Precautionary statements: \* P102: Keep out of reach of children.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P405: Store locked up.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P261: Avoid breathing vapours.

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED HEAVY - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-150-3	64742-48-9	Xn: R65; -: R10; -: R66; -: R67	-	30-50%

[cont...]

# SAFETY DATA SHEET

EXTRA GLOSS PROTECTION

Page: 3

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

265-150-3	64742-48-9	Xn: R65; -: R10; -: R66	Asp. Tox. 1: H304; Flam. Liq. 3: H226	30-50%
-----------	------------	-------------------------	---------------------------------------	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the

[cont...]

# SAFETY DATA SHEET

## EXTRA GLOSS PROTECTION

Page: 4

contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Refer to section 13 of SDS for disposal considerations.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Nitrile gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

[cont...]

# SAFETY DATA SHEET

EXTRA GLOSS PROTECTION

Page: 5

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Beige

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Not miscible

Viscosity: Non-viscous

Viscosity test method: Flow time in seconds in a 3 mm ISO cup (ISO 2431)

Boiling point/range°C: 150

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 36

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.775 - 0.790

pH: Not applicable.

VOC g/l: No data available.

### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

EXTRA GLOSS PROTECTION

Page: 6

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

NAPTHA (PETROLEUM) HYDROTREATED HEAVY

IHL	RAT	LD50	35	mg/kg
ORL	RAT	LD50	2000	mg/kg

Toxicity values: No data available.

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.  
There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

### 12.1. Toxicity

Hazardous ingredients:

NAPTHA (PETROLEUM) HYDROTREATED HEAVY

-	72H IC50	>100	mg/l
-	48H EC50	1.0	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

[cont...]

# SAFETY DATA SHEET

EXTRA GLOSS PROTECTION

Page: 7

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Waste code number: 140603

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

UN number: UN1263

### 14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL  
(LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),  
HYDROTREATED HEAVY)

### 14.3. Transport hazard class(es)

Transport class: 3

### 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

[cont...]

# SAFETY DATA SHEET

## EXTRA GLOSS PROTECTION

Page: 8

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H336: May cause drowsiness or dizziness.  
R10: Flammable.  
R65: Harmful: may cause lung damage if swallowed.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect level  
DNEL = derived no effect level  
LD50 = median lethal dose  
LC50 = median lethal concentration  
EC50 = median effective concentration  
IC50 = median inhibitory concentration  
dw = dry weight  
bw = body weight  
cc = closed cup  
oc = open cup  
MUS = mouse  
GPG = guinea pig  
RBT = rabbit  
HAM = hamster  
HMN = human  
MAM = mammal  
PGN = pigeon  
IVN = intravenous  
SCU = subcutaneous  
SKN = skin  
DRM = dermal  
OCC = ocular/corneal  
PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.